

## Fault tolerant dynamical decoders for topological quantum memories

Mon, 2016-06-20 10:54 - [Martin Kliesch](#) [1] **Date:** 2015-11-01 - 2016-06-20

**Author(s):**

M. Herold, M. J. Kastoryano, E. T. Campbell, J. Eisert

**Reference:**

arXiv:1511.05579

**URL:**

<http://arxiv.org/abs/1511.05579> [2]

Active error correction of topological quantum codes - in particular the toric code - remains one of the most viable routes to large scale quantum information processing. In this work, we introduce the concept of a dynamical decoder as a promising route for achieving fault-tolerant quantum memories. We analyze a specific dynamical decoder based on a discrete time cellular automaton decoder and provide evidence of a threshold above 0.05% with measurement errors. Without measurement errors, the threshold increases by a factor of roughly 1.5. We stress that (asynchronous) dynamical decoding gives rise to a Markovian dissipative process, hence equating cellular automaton decoding to a fully dissipative topological quantum memory, which removes errors continuously. Finally, we analyze the required resources, and speculate about an ideal constant resource dynamical decoder.

- [Quantum Computation](#) [3]
- [13.30.+t Fault-tolerant quantum computation](#) [4]
- [Result](#) [5]
- [SIQS](#) [6]

**Source URL:**

<http://qurope.eu/db/publications/fault-tolerant-dynamical-decoders-topological-quantum-memories>

**Links:**

[1] <http://qurope.eu/users/kliesch>

[2] <http://arxiv.org/abs/1511.05579>

[3] <http://qurope.eu/category/virtual-institute/quantum-computation>

[4] <http://qurope.eu/category/qics/10-quantum-computation/13-defeating-errors/1330t-fault-tolerant-quantum-computation>

[5] <http://qurope.eu/category/attribute/result>

[6] <http://qurope.eu/category/projects/ips/siqs>